



345 "HOT" BLOCK FILLER (SMOOTH)

DESCRIPTION

An Ethylene Chloride-Vinyl Acetate Latex based block filler especially formulated for use over "HOT" block and stucco. **Anvil #345** provides a uniform base for application of more costly finish coats which would otherwise be absorbed by an unsealed surface requiring additional recoats to achieve uniform appearance. The unique properties of this product allow it to lock in alkalinity, resist efflorescence, and deterioration caused by moisture. **Anvil #345 "HOT" Block Filler** prevents "burn through" caused by high pH in new stucco or masonry.

USES

To prime, fill, and seal pores in rough stucco, concrete block, cement and plaster and prevent pH burn through.

SURFACE PREPARATION

Remove all loose dirt, chalk, mildew and other surface contaminants. Pressure clean and apply mildewcide for proper preparation for exterior surfaces. May be tinted to permit the use of economical, lower hiding topcoats.

THINNING

None required. Use water if desired. 1/2 Pt. per Gallon is permissible.

APPLICATION

Use brush, roller or spray. Best results are obtained when using airless spray equipment for more porous applications.

LIMITATION OF LIABILITY

This product is manufactured to rigid control specifications. It is impossible to control the use and application. Therefore, the manufacturer's sole liability is limited to replacing quantities of product proven to be defective. The manufacturer disclaims any liability for the cost of labor to repaint or any other use of the product.

Page 1 of 2

TECHNICAL DATA

PRODUCT NUMBER: 345

RESIN: Ethylene Chloride Vinyl Acetate

COLOR: White

GLOSS: Flat

SOLID CONTENT:

BY WEIGHT -55%

BY VOLUME - 40%

RECOMMENDED COVERAGE:

75 to 150 Sq.Ft per Gallon at recommended dry film thickness 4 to 8 Mills. D.F.T. includes material which has been used to fill the pores of rough block, masonry, etc.

% PIGMENT BY WEIGHT: 38

%VEHICLE BY WEIGHT: 62

VISCOSITY: 120 KU

WEIGHT PER GALLON: 11.4 lbs.

FLASH POINT: None

DRYING TIME: 70 F 50% R.H

Touch - 1/2 to 1 hour

Recoat - 2 to 3 hours

Dry - 4 to 6 hours

Do not apply when rain, cold or nightfall is imminent. do not apply at temp. below 50 F

Drying and cure times are influenced by ambient temp. and relative humidity.

THINNER/CLEANUP: Water

TINTING: Light tones only

VOC: 74.3 grams/liter

AVAILABLE IN 5 GALLON PAIL ONLY

Revised 1-09 Supersedes all prior publications GRO

WARNING! WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.

Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! IRRITANT! HARMFUL IF SWALLOWED. IF TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST.

WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID; if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.