Minimize your risk with Challenging Glazing applications... Heat soak test your fully tempered glass.



JEB offers 100% heat soak testing for 1/4" through 3/4" uncoated or pyrolytic low-e glass that is typically used in demanding or higher risk glazing applications.



- Structural Glass Walls
- Handrails
- Doors
- Insulating Glass
- Canopies
- Overhead Glazing
- Laminated Glass



Processed in compliance with European Standards EN 14179-1:2005.

Call JEB at 800-257-7827!

The Architects Choice

JEBERKOWITZ, LP

ARCHITECTURAL GLASS SINCE 1920

One Gateway Boulevard, P.O. Box 427, Pedricktown, NJ 08067 PHONE: (800) 257-7827 FAX: (856) 299-4344 www.jeberkowitz.com

JEBERKOWITZ, LP

ARCHITECTURAL GLASS SINCE 1920

TECHNICAL SUPPORT


- Glass Performance Data
- LBNL Windows 5.2, Optics 5
- Thermal Stress Analysis
- Glass Deflection
- Submittal Samples

- Architectural Binders
- EZ Specification Change Program
- Architectural Presentations
- LEED® Documentation & Sustainable Project Assistance


PRODUCTS




- Tempering
 - 1/4"
 - 3/8"
 - 1/2"
 - 3/4"
 - 5/8" (consult factory)
- InsulatingBlack & Gray Sealants
- Spandrel8 Standard Colors
- Silk Screening
 - 1/8" Dots & Lines
 - Custom Patterns Available



- Monolithic
- Insulated Glass
- Canopies



- Swing
- Sliding
- Stacking



















J. E. Berkowitz, L. P. One Gateway Boulevard P.O. Box 427 Pedricktown, NJ 08067 (800)257-7827 Fax(856)299-4344



Our email address is: info@jeberkowitz.com

www.jeberkowitz.com